

PLC SERIES RELAYS



TECHNICAL SPECIFICATIONS

TYPE		PLC	
TERMINAL TYPE		PCB	
CONTACT CONFIGURATION		1NO / 1C	
RATED CARRYING CURRENT (RESISTIVE) AT 24 VDC / 250 VAC		40A	NO : 40A NC : 30A
CONTACT MATERIAL		Silver alloy	
INITIAL CONTACT RESISTANCE (MAX)		0.050 Ω	
COIL NOMINAL VOLTAGES	DC	12 - 24 V	
	AC	-	
OPERATING POWER FOR DC COIL		0.87 - 0.9 W	
DIELECTRIC STRENGTH BETWEEN	OPEN CONTACT	1500 VAC	
	COIL TO CONTACT	2500 VAC	
INSULATION RESISTANCE AT 500 VDC AT 27°C & 65% RH		1000 M Ω	
OPERATE TIME (MAX)		10 ms	
RELEASE TIME (MAX)		8 ms	
AMBIENT TEMPERATURE		-40°C To + 85°C	
ELECTRICAL LIFE (NO OF OPERATIONS)		10 ⁵	
MECHANICAL LIFE (NO OF OPERATIONS)		10 ⁶	
ALL DIMENSIONS ARE IN mm (W x L x H)		32.4 x 27.5 x 28(+5.0)	
MAX WEIGHT IN GRAMS		35 gms (approx)	
STANDARDS		IEC 61810-1	



SALIENT FEATURES

- Miniature
- PCB Mountable
- High Reliability

APPLICATIONS

- | | | |
|----------------------------|-------------|---------------|
| • Air Condition Equipments | • Heaters | • Automobiles |
| • Battery Chargers | • Inverters | • Controllers |

NOTE:-


- 1) All Specification / Dimensions subject to Tolerance.
- 2) Any Techno commercial changes is / are prerogative of manufacturer / management of the company which can be done without any notice.




COIL – DATA (ALL VALUES AT 27°C ± 2°AMBIENT, COLD START)

NOMINAL VOLTAGE (V)	RESISTANCE IN OHM'S ± 10% Ω	MUST OPERATE VOLTAGE (V)	MUST RELEASE VOLTAGE (V)	OPERATING POWER FOR COIL DC COIL (W)
12 V	160	9	1.2	0.9
24 V	640	18	2.4	0.9

ORDERING CODE FOR RELAY



DIMENSIONS



NOTE :- 1) In case no tolerance shown in outline dimensions : Outline dimension 1mm, tolerance should be ±0.2mm
Outline dimension 1mm and 5mm, tolerance should be ±0.3mm Outline dimension 5mm tolerance should be ±0.4mm
2) The tolerance without indicating for PCB layout is always ±0.2mm



+91 22 25106104/05



+91 7045459530



sales@plarelays.com



www.plarelays.com